



# ROOFING AND INDUSTRIAL HYBRID SEALANT

& HIGH PERFORMANCE CONSTRUCTION ADHESIVE

## ADHESION TO:

**ALUMINUM - ASPHALT - GLASS - PVC - TPO - WOOD - METAL - SILICONE - PAINTED SURACES**

- WET SURFACES
- EXTERIOR GRADE
- WATERPROOF
- APPLICATION TEMPERATURES FROM -40 DEGREES TO 200 DEGREES F.
- 100% SOLIDS - NON-SHRINK
- PLASTICIZER AND SOLVENT FREE
- PAINTABLE
- HIGH FLEXIBILITY
- 'EASY TO APPLY' CONSISTENCY
- LOW ODOR TECHNOLOGY

## DESCRIPTION

- One Component 100% solids, plasticizer-free, paintable Hybrid Silicone-Urethane Sealant
- EASY TO APPLY technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Plasticizer free formulation prevents residue formation on surface in lower temperature applications and discoloration of topcoats from yellowing and dirt pickup.
- No plasticizer also means product will retain its initial flexibility for the many times longer.
- 100% SOLIDS – SOLVENT FREE NON-SHRINK FORMULATION
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to ice- free surfaces at or below freezing temperatures
- Performance at temperatures as low as -40 degrees F.
- Even bonds to damp or wet surfaces and is rain tolerant during cure.
- Cures to a Waterproof tough flexible sealant.
- Unlike competitors, Gun-able even if material is at freezing temperatures
- Non-staining and mildew resistant.
- UV resistant.

## RECOMMENDED USES

Industrial uses requiring high elasticity, high-strength and outstanding adhesion for a wide-range of substrates WETSEAL bonds aggressively to steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete and coated metals.

Property	Result
<b>Tensile Strength:</b>	<b>250 psi</b>
<b>Elongation at break:</b>	<b>300%</b>
<b>Hardness Shore A</b>	<b>32 (5 day ambient cure)</b>
<b>Application Temperature</b>	<b>13°F to 200°F</b>
<b>Density</b>	<b>10.5 lbs/gal</b>
<b>Low Temp Flex</b>	<b>-20 °F</b>
<b>Service Temp</b>	<b>-40°F to 200°F</b>
<b>Shelf Life (when stored @ 40°F to 80°F)</b>	<b>12 months</b>

## COLORS

- White

## PACKAGING/SHIPPING INFORMATION

CONTAINER SIZE	SHIPPING CLASS
10.3 and 28 fl. oz.	Class 55
2 Gallon pail (7.6 liters)	Class 55

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Used must contact Everest systems Company to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Everest Systems Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY EVEREST SYSTEMS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.